



LED
CYLINDRICAL
PMMA

Code	Power	Feeding	Colour temperature	Brilliance	Ø tube	Length	Body	IP	IK	Class	Power cable	Fixing
LONG TLED40-24 TLED40-230	1 LED TUBE 40 W	24 V ca/ac 230 V	6500 K	6690 lm	70 mm	1510 mm	CYLINDRICAL IN PMMA SCRATCH-RESISTANT	IP67	IK07	III II	ABSENT	2 LOCKING BRACKETS
MEDIUM TLED18-24 TLED18-230*	1 LED TUBE 18 W	24 V ca/ac 230 V	6500 K	3060 lm	70 mm	707 mm	CYLINDRICAL IN PMMA SCRATCH-RESISTANT	IP67	IK07	III II	ABSENT	2 LOCKING BRACKETS
SHORT TLED12-24 TLED12-230	1 LED TUBE 12 W	24 V ca/ac 230 V	6500 K	2100 lm	70 mm	505 mm	CYLINDRICAL IN PMMA SCRATCH-RESISTANT	IP67	IK07	III II	ABSENT	2 LOCKING BRACKETS

LED
CYLINDRICAL
GLASS

LONG VTLED40-24 VTLED40-230	1 LED TUBE 40 W	24 V ca/ac 230 V	6500 K	6690 lm	70 mm	1510 mm	CYLINDRICAL IN BOROSILICATE GLASS	IP67	IK07	III II	ABSENT	2 LOCKING BRACKETS
MEDIUM VTLED18-24 VTLED18-230*	1 LED TUBE 18 W	24 V ca/ac 230 V	6500 K	3060 lm	70 mm	707 mm	CYLINDRICAL IN BOROSILICATE GLASS	IP67	IK07	III II	ABSENT	2 LOCKING BRACKETS
SHORT VTLED12-24 VTLED12-230	1 LED TUBE 12 W	24 V ca/ac 230 V	6500 K	2100 lm	70 mm	505 mm	CYLINDRICAL IN BOROSILICATE GLASS	IP67	IK07	III II	ABSENT	2 LOCKING BRACKETS

FLUORESCENT
CYLINDRICAL
PMMA

LONG TFTL36-24 TFTL36-230*	1 FLUORESCENT TUBE 36 W	24 V 2G13 230 V 2G13	6500 K	3350 lm	70 mm	1510 mm	CYLINDRICAL IN PMMA SCRATCH-RESISTANT	IP67	IK07	III I	ABSENT	2 LOCKING BRACKETS
MEDIUM TFC36-24 TFC36-230*	1 COMPACT FLUORESCENT TUBE 36 W	24 V 2G11 230 V 2G11	6500 K	2900 lm	70 mm	707 mm	CYLINDRICAL IN PMMA SCRATCH-RESISTANT	IP67	IK07	III I	ABSENT	2 LOCKING BRACKETS
SHORT TFC18-24 TFC18-230*	1 COMPACT FLUORESCENT TUBE 18 W	24 V 2G11 230 V 2G11	6500 K	1200 lm	70 mm	505 mm	CYLINDRICAL IN PMMA SCRATCH-RESISTANT	IP67	IK07	III I	ABSENT	2 LOCKING BRACKETS

FLUORESCENT
CYLINDRICAL
GLASS

LONG VTFTL36-24 VTFTL36-230*	1 FLUORESCENT TUBE 36 W	24 V 2G13 230 V 2G13	6500 K	3350 lm	70 mm	1510 mm	CYLINDRICAL IN BOROSILICATE GLASS	IP67	IK07	III I	ABSENT	2 LOCKING BRACKETS
MEDIUM VTFC36-24 VTFC36-230*	1 COMPACT FLUORESCENT TUBE 36 W	24 V 2G11 230 V 2G11	6500 K	2900 lm	70 mm	707 mm	CYLINDRICAL IN BOROSILICATE GLASS	IP67	IK07	III I	ABSENT	2 LOCKING BRACKETS
SHORT VTFC18-24 VTFC18-230*	1 COMPACT FLUORESCENT TUBE 18 W	24 V 2G11 230 V 2G11	6500 K	1200 lm	70 mm	505 mm	CYLINDRICAL IN BOROSILICATE GLASS	IP67	IK07	III I	ABSENT	2 LOCKING BRACKETS

*Also available in 115 V version. For code replace 115 to 230.

The watertight ceiling lights are particularly suitable to illuminate the working area of the machine tool where it needs a well stratified linear illumination of both the spindle and the working area.

